

FLAMINGO M10/156D 625-630W

Supreme Quality



High Quality



Low Power Loss

High Quality and Low Power Loss ensure high efficiency and long lifespan.



High Power Output



Reliability and Protection

High Power Output and Reliability ensure consistent performance and protection against environmental factors.

Module Characteristics


12-Year

30-Year

1%

0.4%

12-Year 30-Year 1% 0.4%



At least 87.4% of nominal power up to 30 years

630W

Maximum Power

22.5%

Maximum Power Coefficient

1%

Temperature Coefficient

0.4%

Temperature Coefficient

Technical Specifications

Table with 2 columns: Parameter (Cell Type, G, M, Glass, Frame, etc.) and Value (N-Type TOPCon, etc.)

Environmental and Safety

Table with 2 columns: Parameter (Temperature, Humidity, etc.) and Value (Operating range, etc.)

Electrical Performance

Table with 2 columns: Parameter (Rearside Power Gain, etc.) and Value (Efficiency, etc.)

Temperature Performance

Table with 2 columns: Parameter (Temperature Coefficient, etc.) and Value (Efficiency, etc.)

Temperature Performance

Table with 2 columns: Parameter (Temperature Coefficient, etc.) and Value (Efficiency, etc.)

Temperature Performance

Table with 2 columns: Parameter (Temperature Coefficient, etc.) and Value (Efficiency, etc.)



Information text below QR code

Gokin

Cable type

Connector type